

LOCK'ER[®] DOWN

SECURITY PRODUCTS

INSTALLATION INSTRUCTIONS

LD2058/LD2058EX

[2006-2022 Dodge Ram 1500,2500, & 3500 and 2019 except 1500 Under Front Bench Seat]

1. For any combination style lock, it is a good idea to set the combination before installing the safe. We recommend that the combination be set with the **DOOR OPEN** in order to test the lock combination effectively without locking yourself out.
2. Clear out the contents of the center console for now, including the factory mat at the bottom of the console.
3. Remove the **4** 10mm bolts from inside the console compartment.
4. Remove the neoprene padding from the bottom of the inside of the safe.
5. Set the safe into the center console.
 - a. Make sure that the **4** slots line up with the four factory bolt locations (**these locations being where you removed bolts from in STEP 3**)
6. Using your 10mm fastening device, insert the **4 LOCK'ER DOWN PROVIDED 10MM BOLTS** into the factory holes at the bottom of the safe (these holes should line up with the factory screw holes at the bottom of the compartment)
7. Tighten the bolts, **DO NOT OVER TIGHTEN, THIS COULD DAMAGE THE CONSOLE.**
8. Re-insert the padding that was removed from the safe before installation.
9. Enjoy your purchase!

Tools Needed:

- **SOCKET WRENCH**
- 10mm Socket bit

Contents Included: **4** 10mm Bolts.



LD2058 Install
Video

